

# 4.7

## Toggle Switches




### Heavy Duty Hesitation Switches

#### Product Selection

4






#### Heavy Duty Hesitation Switches—One-Hole Panel Mount

Rating	Poles and Throw <sup>②</sup>	Circuit with Toggle in ...			Base Circuit See Page V11-T4-35	Bushing Length "A" Inches (mm)	Lever Length "B" Inches (mm)	Lever Type	Catalog Number		
		UP Position 	CENTER Position 	DOWN Position (Keyway) 					Solder Terminals	Screw Lugs	0.250 in Spade Terminals
15A, 125 Vac <sup>①</sup> 10A, 250 Vac 3/4 hp, 250 Vac	2PDT	ON	OFF	ON	D	0.468 (11.89)	0.687 (17.45)	Bat	<b>7992K11</b>	<b>7992K10</b>	<b>7992K12</b>
15A, 125 Vac <sup>①</sup> 10A, 250 Vac 3/4 hp, 250 Vac	3PDT	ON	OFF	ON	F	0.468 (11.89)	0.687 (17.45)	Bat	<b>7991K11</b>	<b>7991K10</b>	<b>7991K12</b>
15A, 125 Vac <sup>①</sup> 10A, 250 Vac 3/4 hp, 250 Vac	4PDT	ON	OFF	ON	F	0.468 (11.89)	0.687 (17.45)	Bat	<b>7990K11</b>	<b>7990K10</b>	<b>7990K12</b>



#### Heavy Duty Hesitation Switches—Flush Mount

Rating	Poles and Throw	Circuit with Toggle in ...			Lever Type	Termination Type	Catalog Number
		UP Position 	CENTER Position 	DOWN Position (Keyway) 			
20A, 125 Vac/Vdc 10A, 250 Vac/Vdc	2PDT	ON	NONE	ON	Square	Screw	<b>7810K1</b>
		ON	OFF	ON	Square	Screw	<b>7810K2</b> <sup>③④</sup>
30A, 125 Vac/Vdc 20A, 250 Vac/Vdc	2PDT	ON	OFF	ON	Square	Screw	<b>7811K5</b> <sup>③⑤</sup>
	3PDT	ON	OFF	ON	Square	Screw	<b>7812K2</b>
	4PDT	ON	OFF	ON	Square	Screw	<b>7813K2</b>

#### Notes

- ① Listed rating for 125 Vac also applies at 28 Vdc.
- ② Supplied in a four-pole base.
- ③ CSA Certified.
- ④ Also rated 5A, 600 Vac; 1-1/2 hp, 250 Vdc; 2 hp, 240 Vac.
- ⑤ Also rated 2 hp, 250 Vac/Vdc.